



Product Function

Suitable for measuring the insulation resistance of electric motor, switch, electrical appliance and other electrical equipment and insulation materials.

Product Feature

1. Max output voltage 5000V, Max test resistance value 1000GΩ, Max short circuit current 2mA
2. Insulation resistance value, test time and output voltage are displayed on the same screen.
3. Safe structure and improved circuit new design, more complete function, higher accuracy, more convenient and reliable operation.
4. Auto discharge and perfect protection circuit, which can effectively prevent the damage of counter voltage.
5. The host equip with large LCD display, white screen and backlight, bar chart indication, clearly and obvious.

Technical Specifications

Model	ETCR3460A	ETCR3460B
Power Supply	DC 1.5V LR14X6PCS	DC 1.5V LR14X6PCS
Rated Voltage	50V; 250V; 500V; 1000V; 2500V	50V; 250V; 500V; 1000V ;2500V; 5000V
Output Voltage Accuracy	(5%~10%) ± 10V	(5%~10%) ± 10V
Insulation Resistance Range	0.1MΩ~200GΩ	0.1MΩ~1000GΩ
Max Insulation Resistance Accuracy	±3%rdg ± 5dgt	±3%rdg ± 5dgt
Voltage Range	AC/DC: 0V~750V	AC/DC: 0V~750V
Voltage Accuracy	±5%rdg ± 5dgt	±5%rdg ± 5dgt
Short Circuit Current	2mA MAX	2mA MAX
Shift	Turn the shift rotary knob to select the gears	
Backlight	Controllable off-white backlight, suitable for dark site	
Display Mode	4 digital LCD display, LCD size: 108mm×65mm	
Meter Dimension	212mm(L)X175mm(W)X76mm(H)	
Weight	Tester: 1230g(include battery); Total weight: 2.4kg(include accessories)	
Battery Voltage	Battery low voltage symbol display, and remind to replace the battery in time	
Automatic Discharge	Automatic discharge the voltage of the measured object, During discharging, ⚠ symbol flash. Discharge finish ⚠ symbol extinguish	
Auto Shutdown	15 minutes without any operation after starting up, the tester will shutdown automatically	
Power Consumption	Standby: about 40mA(backlight off); Start up with backlight: about 50mA; Measurement: about 100mA(backlight off)	
Working Environment	-10℃~40℃; Below 80%RH	
Suitable Safety Standard	IEC61010-1(CAT III 300V, CAT IV 150V, Pollution 2)	
Accessories	Tester:1PCS; High voltage probe teste line: 1PCS red; Pen probe test line: 1PCS black; Alligator clip test line: 1PCS black; Alligator clip: 1PCS(black);Tool bag: 1PCS	